



ATLANTIC CONTAINMENT

BUILDING QUALITY STEEL STORAGE TANKS SINCE 1992

ROUND HORIZONTAL CYLINDRICAL TANKS



AC500KD — DW HORIZ. SKID



AC500KD-HD2 — DW HORIZ. PIPE SKID



AC2KKD-HD3 — DW HORIZ PIPE SKID

PRODUCT DETAILS

Atlantic Containment's single wall & double wall round horizontal tanks are engineered to meet and exceed all requirements for industrial bulk oil needs. AC produces an extensive line of standard size models that can help fit your space restraints. Supported and Skid versions are available. With our newly released IC "Intimate Contact" designs, less space is taken so you can have more space to work around. Durable carbon steel construction make these dependable and more resistant to work place collisions. Each tank is engineered to be reliable and safe for years of use. From job sites, industrial facilities, construction zones and residential, we can create a containment solution that works.

STANDARD TANK SPECS

- CAPACITY: 300– 4,000 GALLONS
- UL-142 (MH15058) / ANSI/NPA CERTIFIED W/ LABEL
- MEETS ALL REQUIREMENTS OF IFC
- HR CARBON STEEL CONSTRUCTION
- 5 PSI FACTORY AIR TESTED W/ QC WELD INSPECTION
- 'HD' LIFTING LUGS FOR EASY TANK INSTALLATION
- SECONDARY MONITORING PIPE STANDARD ON DW
- NPT FITTINGS FOR ATMOSPHERIC & EMERGENCY VENTING, PRODUCT TILL & MONITORING GAUGE
- EXTERIOR PRIMER PAINT FINISH STANDARD (ENAMEL & URETHANE COLORS AVAILABLE)

FLUID CONTAINMENT SPECS

- ⇒ UNUSED CLASS IIIB COMBUSTIBLE MOTORS OILS & FLUIDS
- ⇒ PRODUCTION CHEMICALS
- ⇒ GASOLINE FUEL
- ⇒ ON-ROAD / OFF-ROAD DIESEL FUEL
- ⇒ KEROSENE FUEL
- ⇒ TRANSMISSION OIL
- ⇒ MACHINE OIL



ROUND CYLINDRICAL TANKS

TANK MODEL	CAPACITY	GAUGE	DIAMETER	OA LENGTH	OA HEIGHT	PART #
HORIZONTAL	300 GAL.	SW - 12GA	38"	61"	42"	AC300HS
HORIZONTAL	500 GAL.	SW - 12GA	48"	61"	51"	AC500HS
HORIZONTAL	1000 GAL.	SW - 10GA	48"	128"	51"	AC1KHS48
HORIZONTAL	1000 GAL.	SW - 10GA	64"	72"	67"	AC1KHS64
HORIZONTAL	1500 GAL.	SW - 10GA	64"	108"	67"	AC1.5KHS
HORIZONTAL	2000 GAL.	SW - 7GA	64"	138"	67"	AC2KHS
HORIZONTAL	3000 GAL.	SW - 7GA	64"	216"	67"	AC3KHS
HORIZONTAL	4000 GAL.	SW - 7GA	64"	286"	67"	AC4KHS
HORIZONTAL	300 GAL.	DW - 12GA	38"	65"	43"	AC300DHS
HORIZONTAL	500 GAL .	DW - 12GA	48"	65"	52"	AC500DHS
HORIZONTAL	1000 GAL.	DW - 10GA	48"	132"	52"	AC1KDHS48
HORIZONTAL	1000 GAL.	DW - 10GA	64"	73"	68"	AC1KDHS64
HORIZONTAL	1500 GAL.	DW - 10GA	64"	113"	68"	AC1.5KDHS
HORIZONTAL	2000 GAL.	DW - 7GA	64"	142"	68"	AC2KDHS
HORIZONTAL	3000 GAL.	DW - 7GA	64"	218"	68"	AC3KDHS
HORIZONTAL	4000 GAL.	DW - 7GA	64"	288"	68"	AC4KDHS
HORIZONTAL	300 GAL.	SW - 12GA	38"	65"	42-1/2"	AC300SK
HORIZONTAL	500 GAL .	SW - 12GA	48"	65"	51-1/2"	AC500SK
HORIZONTAL	1000 GAL.	SW - 10GA	48"	133"	51-1/2"	AC1KSK48
HORIZONTAL	1000 GAL.	SW - 10GA	64"	77"	67-1/2"	AC1KSK64
HORIZONTAL	1500 GAL.	SW - 10GA	64"	113"	67-1/2"	AC1.5KSK
HORIZONTAL	2000 GAL.	SW - 7GA	64"	144"	67-1/2"	AC2KSK
HORIZONTAL	3000 GAL.	SW - 7GA	64"	222"	67-1/2"	AC3KSK
HORIZONTAL	4000 GAL.	SW - 7GA	64"	293"	67-1/2"	AC4KSK
HORIZONTAL	300 GAL.	DW - 12GA	38"	80"	43-1/2"	AC300KD
HORIZONTAL	500 GAL .	DW - 12GA	48"	80"	52-1/2"	AC500KD
HORIZONTAL	1000 GAL.	DW - 10GA	48"	148"	52-1/2"	AC1KKD48
HORIZONTAL	1000 GAL.	DW - 10GA	64"	89"	68-1/2"	AC1KKD64
HORIZONTAL	1500 GAL.	DW - 10GA	64"	117"	68-1/2"	AC1.5KKD
HORIZONTAL	2000 GAL.	DW - 7GA	64"	154"	68-1/2"	AC2KKD
HORIZONTAL	3000 GAL.	DW - 7GA	64"	233"	68-1/2"	AC3KKD
HORIZONTAL	4000 GAL.	DW - 7GA	64"	303"	68-1/2"	AC4KKD

- Heavy Duty Lifting lugs for vertical lifting and maneuvering of tank during installation
- ***NEW** Secondary E-box Emergency Vent Designs For IC, minimizing overall size and weight
- Air pressure tested to ensure a 100% leak-proof tank @ 5psi
- **Phosphate coated steel to maximize tank life, eliminate corrosion**
- **Pre-oiled internally before delivery to prevent interior rust**
- Standard external 2" monitoring pipe for DW horizontal
- Finished red oxide primer exterior coating
- Optional enamel & urethane colors available
- Optional 110% DW containment designs available
- HD Pipe Skid Upgrades available (2", 3", 4" DIA)

